

SHIBALLOY®

CARBIDE BURRS SINCE 1983

Field Testing
Of Burrs

100% Braze
Testing

Quality
Materials &
Supply Chain

State Of Art
Manufacturing
Equipment

Attentive
Customer
Service

Stock For
Regular
Customer

Latest Burr
Design &
Geometry

Experienced
Team

CYLINDRICAL	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Brazed	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SA-42	3/32	7/16	1/8	1 1/2	S	•	•	•
SA-42 L2"	3/32	7/16	1/8	2	S	•	•	
SA-42 L3"	3/32	7/16	1/8	3	S	•	•	
SA-43	1/8	9/16	1/8	1 1/2	S	•	•	
SA-43 L2"	1/8	9/16	1/8	2	S	•	•	
SA-43 L3"	1/8	9/16	1/8	3	S	•	•	
SA-52	5/32	1/2	1/8	2	S	o	o	
SA-52B	5/32	1/2	1/8	2	B	•	•	
SA-53	3/16	1/2	1/8	2	S	o	o	
SA-53B	3/16	1/2	1/8	2	B	•	•	
SA-51	1/4	1/2	1/8	2	B	•	•	
SA-81	3/16	1/2	3/16	2	S	•	•	
SA-11	1/8	1/2	1/4	2	S	o	o	
SA-11B	1/8	1/2	1/4	2 1/2	B	•	•	
SA-12	1/8	5/8	1/4	2	S	o	o	
SA-12B	1/8	5/8	1/4	2 1/2	B	•	•	
SA-13	5/32	5/8	1/4	2	S	•	•	
SA-13B	5/32	5/8	1/4	2 1/2	S	•	•	
SA-14	3/16	5/8	1/4	2	S	•	•	
SA-14B	3/16	5/8	1/4	2 1/2	B	•	•	
SA-1	1/4	5/8	1/4	2	S	•	•	
SA-1L	1/4	1	1/4	2	S	•	•	
SA-1 L6"	1/4	5/8	1/4	6 5/8	B	•	•	
SA-1 NF	1/4	3/4	1/4	2	S			•
SA-2	5/16	3/4	1/4	2 1/2	B	•	•	
SA-3	3/8	3/4	1/4	2 1/2	B	•	•	•
SA-3 L6"	3/8	3/4	1/4	6 3/4	B	•	•	•
SA-3L	3/8	1	1/4	2 3/4	B	o	o	
SA-3X	3/8	1	1/4	2 3/4	B	o	o	
SA-4	7/16	1	1/4	2 3/4	B	o	o	
SA-5	1/2	1	1/4	2 3/4	B	•	•	•
SA-5 L6"	1/2	1	1/4	6 1/2	B	•	•	•
SA-6*	5/8	1	1/4	2 3/4	B	•	•	•
SA-15*	3/4	1/2	1/4	2 1/4	B	o	o	
SA-16*	3/4	3/4	1/4	2 1/2	B	o	o	
SA-7*	3/4	1	1/4	2 3/4	B	o	o	o
SA-7 NF 3/8	3/4	1	3/8	3	B			o
SA-8*	7/8	1	1/4	2 3/4	B	o	o	
SA-9*	1	1	1/4	2 3/4	B	o	o	

CYLINDRICAL END CUT	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Brazed	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SB-42	3/32	7/16	1/8	1 1/2	S	•	•	
SB-42 L2"	3/32	7/16	1/8	2	S	•	•	
SB-42 L3"	3/32	7/16	1/8	3	S	•	•	
SB-ECO	1/8		1/8	3	S	•		
SB-43	1/8	9/16	1/8	1 1/2	S	•	•	
SB-43 L2"	1/8	9/16	1/8	2	S	•	•	
SB-43 L3"	1/8	9/16	1/8	3	S	•	•	
SB-51	1/4	3/16	1/8	1	B	•	•	
SB-11	1/8	1/2	1/4	2	S	o	o	
SB-11B	1/8	1/2	1/4	2 1/2	S	•	•	
SB-12	1/8	5/8	1/4	2	S	o	o	
SB-12B	1/8	5/8	1/4	2 1/2	B	•	•	
SB-13	5/32	5/8	1/4	2	S	o	o	
SB-13B	5/32	5/8	1/4	2 1/2	B	•	•	
SB-14	3/16	5/8	1/4	2	S	o	o	
SB-14B	3/16	5/8	1/4	2 1/2	S	•	•	
SB-1	1/4	5/8	1/4	2	S	•	•	
SB-1B	1/4	5/8	1/4	2	B	•	•	
SB-1L	1/4	1	1/4	2	S	•	•	
SB-1 NF	1/4	3/4	1/4	2	S			•
SB-2	5/16	3/4	1/4	2 1/2	B	•	•	
SB-3	3/8	3/4	1/4	2 1/2	B	•	•	•
SB-3L	3/8	1	1/4	2 3/4	B	•	•	
SB-3X	3/8	1 1/2	1/4	3 1/4	B	o	o	
SB-4	7/16	1	1/4	2 3/4	B	o	o	
SB-5	1/2	1	1/4	2 3/4	B	•	•	•
SB-6*	5/8	1	1/4	2 3/4	B	•	•	•
SB-15*	3/4	1/2	1/4	2 1/4	B	o	o	
SB-16*	3/4	3/4	1/4	2 1/2	B	o	o	
SB-7*	3/4	1	1/4	2 3/4	B	o	o	o
SB-7 NF-3/8	3/4	1	3/8	3	B			o
SB-8*	7/8	1	1/4	2 3/4	B	o	o	
SB-9*	1	1	1/4	2 3/4	B	o	o	

• - EX STOCK/QUICK DELIVERY 0 - LEAD TIME REQUIRED
*- OPTIONAL 3/8" SHANK or 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye
Protection!



Wear Hearing
Protection!




Observe the recommended
rotational speed, especially when
using burrs with long shanks!

CYLINDRICAL RADIUS END	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Brazed	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SC-41	3/32	7/16	1/8	1 1/2	S	●	●	
SC-42	1/8	9/16	1/8	1 1/2	S	●	●	
SC-42 L2"	1/8	9/16	1/8	2	S	●	●	
SC-42 L3"	1/8	9/16	1/8	3	S	●	●	
SC-52	5/32	1/2	1/8	1 1/2	S	○	○	
SC-52B	5/32	1/2	1/8	1 1/2	B	●	●	
SC-53	3/16	1/2	1/8	1 1/2	S	○	○	
SC-53B	3/16	1/2	1/8	1 1/2	B	●	●	
SC-51	1/4	1/2	1/8	2	B	●	●	
SC-81	3/16	1/2	3/16	2	S	●	●	
SC-11	1/8	1/2	1/4	2	S	○	○	
SC-11B	1/8	1/2	1/4	2	B	●	●	
SC-12	1/8	5/8	1/4	2	S	○	○	
SC-12B	1/8	5/8	1/4	2	B	●	●	
SC-13	5/32	5/8	1/4	2	S	●	●	
SC-13B	5/32	5/8	1/4	2	B	●	●	
SC-14	3/16	5/8	1/4	2	S	●	●	
SC-14B	3/16	5/8	1/4	2	B	●	●	
SC-1	1/4	5/8	1/4	2	S	●	●	
SC-1B	1/4	5/8	1/4	2	B	●	●	
SC-11B	1/8	1/2	1/4	2	B	●	●	
SC-1 L6"	1/4	5/8	1/4	6 1/2	B	●	●	
SC-1L	1/4	1	1/4	2	S	●	●	
SC-1 NF	1/4	3/4	1/4	2	S			●
SC-2	5/16	3/4	1/4	2 1/2	B	●	●	
SC-3	3/8	3/4	1/4	2 1/2	B	●	●	●
SC-3 L6"	3/8	3/4	1/4	6 3/4	B	●	●	
SC-3L	3/8	1	1/4	2 3/4	B	○	○	
SC-3X	3/8	1 1/2	1/4	3 1/4	B	○	○	
SC-4	7/16	1	1/4	2 3/4	B	○	○	
SC-5	1/2	1	1/4	2 3/4	B	●	●	●
SC-5 L6"	1/2	1	1/4	7	B	●	●	
SC-6*	5/8	1	1/4	2 3/4	B	●	●	●
SC-15*	3/4	1/2	1/4	2 1/4	B	○	○	
SC-16*	3/4	3/4	1/4	2 1/2	B	○	○	
SC-7*	3/4	1	1/4	2 3/4	B	○	○	○
SC-7 NF-3/8	3/4	1	3/8	3	B			○
SC-9*	1	1	1/4	2 3/4	B	○	○	



● - EX STOCK/QUICK DELIVERY ○ - LEAD TIME REQUIRED
 *- OPTIONAL 3/8" SHANK or 8mm Metric.

 www.P65Warnings.ca.gov



BALL	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Brazed	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SD-41	3/32	3/32	1/8	1 1/2	S	●	●	
SD-42	1/8	1/8	1/8	1 1/2	S	●	●	
SD-42 L2"	1/8	1/8	1/8	2	S	●	●	
SD-42 L3"	1/8	1/8	1/8	3	S	●	●	
SD-52	5/32	5/32	1/8	1 5/8	S	○	○	
SD-52B	5/32	5/32	1/8	1 5/8	B	●	●	
SD-53	3/16	5/32	1/8	1 7/16	S	○	○	
SD-53B	3/16	5/32	1/8	1 7/16	B	●	●	
SD-51	1/4	7/32	1/8	1 3/4	B	●	●	
SD-81	3/16	5/32	3/16	2	S	●	●	
SD-11	1/8	3/32	1/4	2	S	○	○	
SD-11B	1/8	3/32	1/4	2	B	●	●	
SD-14	3/16	1/8	1/4	2	S	●	●	
SD-14B	3/16	1/8	1/4	2	B	●	●	
SD-1	1/4	7/32	1/4	2	S	●	●	
SD-1B	1/4	7/32	1/4	2	B	●	●	
SD-1 L6"	1/4	7/32	1/4	6 1/4	B	●	●	
SD-2	5/16	1/4	1/4	2	B	●	●	
SD-3	3/8	5/16	1/4	2 1/16	B	●	●	●
SD-3 L6"	3/8	5/16	1/4	6 3/8	B	●	●	●
SD-4	7/16	3/8	1/4	2 1/8	B	○	○	
SD-5	1/2	7/16	1/4	2 3/16	B	●	●	●
SD-5 L6"	1/2	7/16	1/4	6 3/16	B	●	●	●
SD-6	5/8	9/16	1/4	2 5/16	B	●	●	●
SD-6 NF-3/8	5/8	9/16	1/4	2 1/2	B			●
SD-7*	3/4	11/16	1/4	2 1/2	B	○	○	○
SD-7 NF-3/8	3/4	11/16	3/8	2 1/2	B			○
SD-9*	1	15/16	1/4	2 3/4	B	○	○	

OVAL	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Brazed	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SE-41	1/8	7/32	1/8	1 1/2	S	●	●	
SE-41 L2"	1/8	7/32	1/8	2	S	●	●	
SE-41 L3"	1/8	7/32	1/8	3	S	●	●	
SE-81	3/16	9/32	3/16	2	S	●	●	
SE-53	3/16	9/32	1/8	2	S	○	○	
SE-53B	3/16	9/32	1/8	2	S	●	●	
SE-51	1/4	3/8	1/8	2 1/8	B	●	●	
SE-11	3/16	5/16	1/4	2	S	●	●	
SE-1	1/4	3/8	1/4	2 1/8	S	●	●	
SE-1B	1/4	3/8	1/4	2 1/8	B	●	●	
SE-1 L6"	1/4	3/8	1/4	6 3/8	B	●	●	
SE-3	3/8	5/8	1/4	2 3/8	B	●	●	●
SE-3 L6"	3/8	5/8	1/4	6 5/8	B	●	●	●
SE-5	1/2	7/8	1/4	2 5/8	B	●	●	●
SE-5 L6"	1/2	7/8	1/4	6 7/8	B	●	●	
SE-6*	5/8	1	1/4	2 3/4	B	●	●	●
SE-7*	3/4	1	1/4	2 3/4	B	○	○	○
SE-7 NF-3/8	3/4	1	3/8	3	B			○

TREE RADIUS END	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SF-41	1/8	1/4	1/8	1 1/2	S	●	●	
SF-42	1/8	1/2	1/8	1 1/2	S	●	●	
SF-42 L2"	1/8	1/2	1/8	2	S	●	●	
SF-42 L3"	1/8	1/2	1/8	3	S	●	●	
SF-53	3/16	1/2	1/8	1 1/2	S	○	○	
SF-53B	3/16	1/2	1/8	1 1/2	S	●	●	
SF-81	3/16	1/2	3/16	2	S	●	●	
SF-51	1/4	1/2	1/8	2	B	●	●	
SF-11	1/8	1/2	1/4	2	S	●	●	
SF-11B	1/8	1/2	1/4	2	B	●	●	
SF-1	1/4	5/8	1/4	2	S	●	●	
SF-1B	1/4	5/8	1/4	2	B	●	●	
SF-1 L6"	1/4	5/8	1/4	6 1/2	B	●	●	
SF-1 NF	1/4	3/4	1/4	2	B			●
SF-3	3/8	3/4	1/4	2 1/2	B	●	●	●
SF-3 L6"	3/8	3/4	1/4	6 3/4	B	●	●	●
SF-4	7/16	1	1/4	2 3/4	B	●	●	
SF-13	1/2	3/4	1/4	2 1/2	B	○	○	
SF-5	1/2	1	1/4	2 3/4	B	●	●	●
SF-5 L6"	1/2	1	1/4	7	B	●	●	●
SF-6*	5/8	1	1/4	2 3/4	B	●	●	●
SF-6* NF	5/8	1	1/4	2 3/4	B			●
SF-7*	3/4	1	1/4	2 3/4	B	○	○	
SF-14*	3/4	1 1/4	1/4	3	B	○	○	○
SF-14 NF-3/8	3/4	1 1/4	3/8	3 1/4	B			○
SF-15*	3/4	1 1/4	1/4	3 1/4	B	○	○	

TREE POINTED END	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SG-41	1/8	1/4	1/8	1 1/2	S	●	●	
SG-42	1/8	5/16	1/8	1 1/2	S	●	●	
SG-43	1/8	3/8	1/8	1 1/2	S	●	●	
SG-44	1/8	1/2	1/8	1 1/2	S	●	●	
SG-44 L2"	1/8	1/2	1/8	2	S	●	●	
SG-44 L3"	1/8	1/2	1/8	3	S	●	●	
SG-81	3/16	1/2	3/16	2	S	●	●	
SG-53	3/16	1/2	1/8	1 1/2	S	○	○	
SG-53B	3/16	1/2	1/8	1 1/2	B	○	○	
SG-51	1/4	1/2	1/8	2	B	●	●	
SG-1	1/4	5/8	1/4	2	S	●	●	
SG-1B	1/4	5/8	1/4	2	B	●	●	
SG-1 L6"	1/4	1/2	1/4	6 1/2	B	●	●	
SG-2	5/16	3/4	1/4	2 1/2	B	●	●	
SG-3	3/8	3/4	1/4	2 1/2	B	●	●	
SG-3 L6"	3/8	3/4	1/4	6 3/4	B	●	●	
SG-13	1/2	3/4	1/4	2 1/2	B	○	○	
SG-5	1/2	1	1/4	2 3/4	B	●	●	●
SG-5 L6"	1/2	1	1/4	1	B	●	●	
SG-6*	5/8	1	1/4	2 3/4	B	●	●	
SG-7*	3/4	1	1/4	2 3/4	B	○	○	
SG-15*	3/4	1 1/2	1/4	3 1/4	B	○	○	

FLAME	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)
SH-41	1/8	1/4	1/8	1 1/2	S	●	●
SH-41 L2"	1/8	1/4	1/8	2	S	●	●
SH-41 L3"	1/8	1/4	1/8	3	S	●	●
SH-53	3/16	3/8	1/8	1 1/2	S	○	○
SH-53B	3/16	3/8	1/8	1 1/2	B	○	○
SH-1	1/4	5/8	1/4	2	S	●	●
SH-1B	1/4	5/8	1/4	2	B	●	●
SH-2	5/16	3/4	1/4	2 1/2	B	●	●
SH-2 L6"	5/16	3/4	1/4	6 3/4	B	●	●
SH-5	1/2	1 1/4	1/4	3	B	●	●
SH-5 L6"	1/2	1 1/4	1/4	7 1/4	B	●	●
SH-6*	5/8	1 7/16	1/4	3 1/5	B	○	○
SH-7*	3/4	1 5/8	1/4	3 3/8	B	○	○

CONE 60° DEGREE	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)
SJ-42	1/8	3/32	1/8	1 1/2	S	●	●
SJ-1	1/4	3/16	1/4	2	S	●	●
SJ-1B	1/4	3/16	1/4	2	B	●	●
SJ-3	3/8	5/16	1/4	2 1/5	B	●	●
SJ-5	1/2	7/16	1/4	2 1/3	B	●	●
SJ-6*	5/8	9/16	1/4	2 7/16	B	●	●
SJ-7*	3/4	11/16	1/4	2 9/16	B	○	○
SJ-9*	1	15/16	1/4	2 7/8	B	○	○

CONE 90° DEGREE	Head Dia	Cut Length	Shank Dia	OAL Length	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)
SK-42	1/8	1/16	1/8	1 1/2	S	●	●
SK-1	1/4	1/8	1/4	2	S	●	●
SK-1B	1/4	1/8	1/4	2	B	●	●
SK-3	3/8	3/16	1/4	2 1/8	B	●	●
SK-5	1/2	1/4	1/4	2 1/4	B	●	●
SK-6*	5/8	5/16	1/4	2 5/16	B	●	●
SK-7*	3/4	3/8	1/4	2 5/16	B	○	○
SK-9*	1	1/2	1/4	2 3/8	B	○	○

● - EX STOCK/QUICK DELIVERY ○ - LEAD TIME REQUIRED
 *- OPTIONAL 3/8" SHANK or 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye Protection!



Wear Hearing Protection!



Observe the recommended rotational speed, especially when using burs with long shanks!

CONE RADIUS END	Head Dia	Cut Length	Shank Dia	OAL Length	Radius Angle	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SL-41	1/8	3/8	1/8	1 1/2	8°	S	●	●	●
SL-42	1/8	1/2	1/8	1 1/2	8°	S	●	●	●
SL-42 L2"	1/8	1/2	1/8	2	8°	S	●	●	●
SL-42 L3"	1/8	1/2	1/8	3	8°	S	●	●	●
SL-53	3/16	1/2	1/8	1 1/2	14°	S	○	○	○
SL-53B	3/16	1/2	1/8	1 1/2	14°	B	●	●	●
SL-81	3/16	7/16	3/16	2	14°	S	●	●	●
SL-1	1/4	5/8	1/4	2	14°	S	●	●	●
SL-1B	1/4	5/8	1/4	2	14°	B	●	●	●
SL-1 L6"	1/4	5/8	1/4	6 3/4	14°	B	●	●	●
SL-2	5/16	7/8	1/4	2 3/4	14°	B	●	●	●
SL-3	3/8	1 1/16	1/4	2 15/16	14°	B	●	●	●
SL-3 L6"	3/8	1 1/16	1/4	7 2/9	14°	B	●	●	●
SL-4	1/2	1 1/8	1/4	3	14°	B	●	●	●
SL-4 L6"	1/2	1 1/8	1/4	7 3/11	14°	B	●	●	●
SL-5*	5/8	1 3/16	1/4	3 1/16	14°	B	●	●	●
SL-6*	5/8	1 5/16	1/4	3 1/5	14°	B	○	○	○
SL-7*	3/4	1 1/2	1/4	3 3/8	14°	B	○	○	○
SL-7 NF-3/8	3/4	1 1/2	3/8	3 5/8	14°	B			

ORDERING CODE:

SA-5 DC - Burr Cylindrical Shape, Double Cut

SA-5M DC - Metric Shank, Burr Cylindrical Shape, Double Cut

SA-5 3/8 DC - Burr Cylindrical Shape, Double Cut, 3/8inch Dia Shank

SA-5M L6" SC - Burr Cylindrical Shape, Single Cut, Metric 6mm Shank 6"
Shank Length

Extended Reach Burrs - 2", 4", 6", 8", 10", 12" Available

Other Available Cuts - Foundry FC/ Chip Breaker CB / Coarse CC / Fine FC /
Diamond DIA / Steel Mill Cut SMC / Inox Mill Cut IMC

CONICAL	Head Dia	Cut Length	Shank Dia	OAL Length	Radius Angle	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)
SM-41	1/8	11/32	1/8	1 1/2	12°	S	●	●
SM-42	1/8	7/16	1/8	1 1/2	14°	S	●	●
SM-42 L2"	1/8	7/16	1/8	2	14°	S	●	●
SM-42 L3"	1/8	7/16	1/8	3	14°	S	●	●
SM-43	1/8	5/8	1/8	1 1/2	7°	S	●	●
SM-53	3/16	1/2	1/8	2	16°	S	○	○
SM-53B	3/16	1/2	1/8	2	16°	B	○	○
SM-51	1/4	1/2	1/8	2 1/8	22°	B	●	●
SM-1	1/4	1/2	1/4	2	22°	S	●	●
SM-1B	1/4	1/2	1/4	2	22°	B	●	●
SM-2	1/4	3/4	1/4	2 1/2	14°	B	●	●
SM-3	1/4	1	1/4	2 3/4	10°	B	●	●
SM-4	3/8	5/8	1/4	2 3/8	28°	B	●	●
SM-5	1/2	7/8	1/4	2 5/8	28°	B	●	●
SM-6*	5/8	1	1/4	2 3/4	31°	B	○	○

INVERTED CONE	Head Dia	Cut Length	Shank Dia	OAL Length	Radius Angle	Solid (Rod) / Braze	Single Cut(SC)	Double Cut(DC)	Aluminium (NF)
SN-41	3/32	1/8	1/8	1 1/2	10°	S	●	●	●
SN-42	1/8	3/16	1/8	1 1/2	10°	S	●	●	●
SN-53	3/16	1/4	1/8	2	10°	S	○	○	○
SN-53B	3/16	1/4	1/8	2	10°	B	●	●	●
SN-51	1/4	1/4	1/8	2	10°	B	●	●	●
SN-81	3/16	1/4	3/16	2	10°	S	○	○	○
SN-1	1/4	5/16	1/4	2	10°	S	●	●	●
SN-1B	1/4	5/16	1/4	2	10°	B	●	●	●
SN-2	3/8	3/8	1/4	2 1/8	13°	B	●	●	●
SN-4	1/2	1/2	1/4	2 1/4	28°	B	●	●	●
SN-6*	5/8	3/4	1/4	2 1/2	18°	B	○	○	○
SN-7*	3/4	5/8	1/4	2 3/8	30°	B	○	○	○

CUT TYPES



SC
Single Cut



DC
Double Cut



DIA
Diamond Cut



FC
Fine Cut



NF
Aluminum Cut



SMC
Steel Mill Cut



IMC
Inox Mill Cut

● - EX STOCK/QUICK DELIVERY ○ - LEAD TIME REQUIRED

* - OPTIONAL 3/8" SHANK or 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye
Protection!



Wear Hearing
Protection!



Observe the recommended
rotational speed, especially when
using burrs with long shanks!

SHIBALLOY®
www.shiballoy.com