

SHIBALLOY®

CARBIDE BURRS SINCE 1983

Field Testing
Of Burrs

100% Braze
Testing

Quality
Materials &
Supply Chain

State Of Art
Manufacturing
Equipment

Attentive
Customer
Service

Stock For
Regular
Customer

Latest Burr
Design &
Geometry

Experienced
Team

CYLINDRICAL	HEAD DIA(MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOLD (ROD) / BRZ	Single Cut (SC)	Double cut (DC)	Aluminium Cut (NF)
SA-42M	2.5	11	3	38	S	•	•	
SA-42M L50	2.5	11	3	50	S	•	•	
SA-42M L75	2.5	11	3	75	S	•	•	
SA-43M	3	14	3	38	S	•	•	
SA-43M L50	3	14	3	50	S	•	•	
SA-43M L75	3	14	3	75	S	•	•	
SA-11M	3	12	6	50	S	○	○	
SA-11MB	3	12	6	54	B	•	•	
SA-12M	3	16	6	50	S	○	○	
SA-12MB	3	16	6	58	B	•	•	
SA-52M	4	12.7	3	50	S	○	○	
SA-52MB	4	12.7	3	50	B	•	•	
SA-13M	4	16	6	50	S	•	•	
SA-13MB	4	16	6	58	B	•	•	
SA-53M	5	12.7	3	50	S	○	○	
SA-53MB	5	12.7	3	50	B	•	•	
SA-14M	5	16	6	50	S	•	•	
SA-14MB	5	16	6	58	B	•	•	
SA-1M	6	16	6	50	S	•	•	•
SA-1MB	6	16	6	60	B	•	•	
SA-1LM	6	25	6	50	S	•	•	
SA-1M L150	6	16	6	166	B	•	•	
SA-51M	6.3	12.7	3	50	B	•	•	
SA-2M	8	19	6	63	B	•	•	
SA-3M	9.5	19	6	63	B	•	•	•
SA-3LM	9.5	25	6	69	B	•	•	
SA-3M L150	9.5	19	6	169	B	•	•	
SA-3MZ	10	20	6	60	B	•	•	
SA-4M	11	25	6	69	B	○	○	
SA-5MZ	12	25	6	65	B	•	•	
SA-5MZ L150	12	25	6	175	B	•	•	
SA-5M	12.7	25	6	69	B	•	•	•
SA-5M L150	12.7	25	6	175	B	•	•	
SA-6M*	16	25	6*	69	B	•	•	•
SA-7M*	19	25	6*	69	B	•	•	○
SA-9M*	25	25	6*	69	B	•	•	

CYLINDRICAL END CUT	HEAD DIA(MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOLD (ROD) / BRZ	Single Cut (SC)	Double cut (DC)	Aluminium Cut (NF)
SB-42M	2.5	11	3	38	S	•	•	
SB-42M L50	2.5	11	3	50	S	•	•	
SB-42M L75	2.5	11	3	75	S	•	•	
SB-43M	3	14	3	38	S	•	•	
SB-43M L50	3	14	3	50	S	•	•	
SB-43M L75	3	14	3	75	S	•	•	
SB-11M	3	12	6	50	S	○	○	
SB-11MB	3	12	6	54	B	•	•	
SB-12M	3	16	6	50	S	○	○	
SB-12MB	3	16	6	58	B	•	•	
SB-13M	4	16	6	50	S	•	•	
SB-13MB	4	16	6	58	B	•	•	
SB-14M	5	16	6	50	S	•	•	
SB-14MB	5	16	6	58	B	•	•	
SB-1M	6	16	6	50	S	•	•	•
SB-1MB	6	16	6	60	B	•	•	
SB-1LM	6	25	6	50	S	•	•	
SB-51M	6.3	4.7	3	43	B	•	•	
SB-2M	8	19	6	63	B	•	•	
SB-3M	9.5	19	6	63	B	•	•	•
SB-3LM	9.5	25	6	69	B	•	•	
SB-3MZ	10	20	6	60	B	•	•	
SB-4M	11	25	6	69	B	○	○	
SB-5MZ	12	25	6	65	B	•	•	•
SB-5M	12.7	25	6	69	B	•	•	•
SB-6 M*	16	25	6*	69	B	•	•	•
SB-7M*	19	25	6*	69	B	○	○	○
SB-9M*	25	25	6*	69	B	○	○	



• - EX STOCK/QUICK DELIVERY 0- LEAD TIME REQUIRED
*- OPTIONAL SHANK 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye
Protection!



Wear Hearing
Protection!



Observe the recommended
rotational speed, especially when
using burrs with long shanks!

CYLINDRICAL RADIUS END	HEAD DIA(MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SC-41M	2.5	11	3	38	S	●	●	
SC-42M	3	14	3	38	S	●	●	
SC-42M L50	3	14	3	50	S	●	●	
SC-42M L75	3	14	3	75	S	●	●	
SC-11M	3	12	6	50	S	○	○	
SC-11MB	3	12	6	54	B	●	●	
SC-12M	3	16	6	50	S	○	○	
SC-12MB	3	16	6	58	B	●	●	
SC-52M	4	12.7	3	50	S	○	○	
SC-52MB	4	12.7	3	50	B	●	●	
SC-13M	4	16	6	50	S	●	●	
SC-13MB	4	16	6	58	B	●	●	
SC-53M	5	12.7	3	50	S	○	○	
SC-53MB	5	12.7	3	50	B	●	●	
SC-14M	5	16	6	50	S	●	●	
SC-14MB	5	16	6	60	B	●	●	
SC-1M	6	16	6	50	S	●	●	●
SC-1MB	6	16	6	60	B	●	●	
SC-1LM	6	25	6	50	S	●	●	
SC-1M L150	6	16	6	166	B	●	●	
SC-51M	6.3	12.7	3	50	B	●	●	
SC-2M	8	19	6	63	B	●	●	
SC-3M	9.5	19	6	63	B	●	●	●
SC-3LM	9.5	25	6	69	B	●	●	
SC-3M L150	9.5	19	6	169	B	●	●	
SC-3MZ	10	20	6	60	B	●	●	
SC-4M	11	25	6	69	B	○	○	
SC-5MZ	12	25	6	65	B	●	●	●
SC-5MZ L150	12	25	6	175	B	●	●	
SC-5M	12.7	25	6	69	B	●	●	●
SC-5M L150	12.7	25	6	175	B	●	●	
SC-6M*	16	25	6*	69	B	●	●	●
SC-7M*	19	25	6*	69	B	●	●	○
SC-9M*	25	25	6*	69	B	●	●	



BALL	HEAD DIA(MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SD-41M	2.5	2.3	3	38	S	●	●	
SD-42M	3	2.8	3	38	S	●	●	
SD-42M L50	3	2.8	3	50	S	●	●	
SD-42M L75	3	2.8	3	75	S	●	●	
SD-11M	3	2.8	6	50	S	○	○	
SD-11MB	3	2.8	6	50	B	●	●	
SD-52M	4	3.4	3	38	S	○	○	
SD-52MB	4	3.4	3	38	B	●	●	
SD-53M	5	4.7	3	38	S	○	○	
SD-53MB	5	4.7	3	38	B	●	●	
SD-14M	5	4	6	50	S	●	●	
SD-14MB	5	4	6	50	B	●	●	
SD-1M	6	5	6	50	S	●	●	●
SD-1MB	6	5	6	50	B	●	●	
SD-1M L150	6	5	6	155	B	●	●	
SD-51M	6.3	5	3	44	B	●	●	
SD-2M	8	6.4	6	50	B	●	●	
SD-3M	9.5	8	6	52	B	●	●	●
SD-3M L150	9.5	8	6	158	B	●	●	
SD-3MZ	10	9	6	49	B	●	●	
SD-4M	11	9.5	6	54	B	○	○	
SD-5MZ	12	10.8	6	51	B	●	●	●
SD-5M	12.7	11	6	55	B	●	●	●
SD-5M L150	12.7	11	6	161	B	●	●	
SD-6M*	16	14	6*	58	B	●	●	●
SD-7M*	19	16	6*	62	B	●	●	○
SD-9M*	25	21	6*	72	B	●	●	

OVAL	HEAD DIA(MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SE-41M	3	5.5	3	38	S	●	●	
SE-41M L50	3	5.5	3	50	S	●	●	
SE-41M L75	3	5.5	3	75	S	●	●	
SE-53M	5	7.1	3	50	S	○	○	
SE-1M	6	9.5	6	50	S	●	●	
SE-1MB	6	9.5	6	55	B	●	●	
SE-1M L150	6	9.5	6	160	B	●	●	
SE-51M	6.3	9.5	3	47	B	●	●	
SE-3M	9.5	16	6	60	B	●	●	●
SE-3M L150	9.5	16	6	166	B	●	●	●
SE-5MZ	12	22	6	66	B	●	●	
SE-5MZ L150	12	22	6	172	B	●	●	
SE-5M	12.7	22	6	66	B	●	●	●
SE-5M L150	12.7	22	6	172	B	●	●	
SE-6M*	16	25	6*	69	B	●	●	○
SE-7M*	19	25	6*	69	B	○	○	○

● - EX STOCK/QUICK DELIVERY 0 - LEAD TIME REQUIRED
 *- OPTIONAL SHANK 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye Protection!



Wear Hearing Protection!



Observe the recommended rotational speed, especially when using burs with long shanks!

TREE RADIUS END	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SF-41 M	3	6	3	38	S	●	●	
SF-42M	3	12.7	3	38	S	●	●	
SF-42M L50	3	12.7	3	50	S	●	●	
SF-42M L75	3	12.7	3	75	S	●	●	
SF-53M	5	12.7	3	50	S	○	○	
SF-11M	3	12.7	6	55	B	●	●	
SF-1M	6	16	6	50	S	●	●	●
SF-1MB	6	16	6	60	B	●	●	
SF-1M L150	6	12.7	6	163	B	●	●	
SF-51M	6.3	12.7	3	50	B	●	●	
SF-3M	9.5	19	6	63	B	●	●	●
SF-3M L150	9.5	19	6	169	B	●	●	●
SF-4M	11	25	6	69	B	●	●	
SF-5MZ	12	25	6	65	B	●	●	●
SF-5MZ L150	12	25	6	175	B	●	●	
SF-5M	12.7	25	6	69	B	○	○	●
SF-5M L150	12.7	25	6	175	B	●	●	●
SF-13M	12.7	19	6	63	B	○	○	
SF-6M*	16	25	6*	69	B	●	●	○
SF-7M*	19	25	6*	69	B	○	○	○
SF-14M*	19	32	6	76	B	○	○	○
SF-15M*	19	38	6	82	B	○	○	

TREE POINTED END	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SG-41M	3	6	3	38	S	●	●	
SG-43M	3	9.5	3	38	S	●	●	
SG-44M	3	12.7	3	38	S	●	●	
SG-44M L50	3	12.7	3	50	S	●	●	
SG-44M L75	3	12.7	3	75	S	●	●	
SG-53M	5	12.7	3	50	S	○	○	
SG-1M	6	16	6	50	S	●	●	
SG-1MB	6	16	6	60	B	●	●	
SG-1M L150	6	12.7	6	163	B	●	●	
SG-51M	6.3	12.7	3	50	B	●	●	
SG-2M	8	19	6	63	B	●	●	
SG-3M	9.5	19	6	63	B	●	●	
SG-3M L150	9.5	19	6	169	B	●	●	
SG-3MZ	10	20	6	60	B	●	●	
SG-5MZ	12	25	6	65	B	●	●	●
SG-5MZ L150	12	25	6	175	B	●	●	
SG-13M	12.7	19	6	63	B	○	○	
SG-5M	12.7	25	6	69	B	●	●	●
SG-5M L150	12.7	25	6	175	B	●	●	
SG-6M*	16	25	6*	69	B	●	●	
SG-7M*	19	25	6*	69	B	○	○	
SG-15M*	19	38	6*	82	B	○	○	

FLAME	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SH-41M	3	6.3	3	38	S	●	●	
SH-41M L50	3	6.3	3	50	S	●	●	
SH-41M L75	3	6.3	3	75	S	●	●	
SH-53M	5	9.5	3	50	S	○	○	
SH-1M	6	16	6	50	S	○	○	
SH-1MB	6	16	6	60	B	●	●	
SH-2M	8	19	6	63	B	●	●	
SH-2M L150	8	19	6	169	B	●	●	
SH-5MZ	12	32	6	76	B	●	●	
SH-5MZ L150	12	32	6	182	B	●	●	
SH-5M	12.7	32	6	76	B	●	●	
SH-5M L150	12.7	32	6	182	B	●	●	
SH-6M*	16	36	6*	80	B	●	●	
SH-7M*	19	41	6*	85	B	○	○	



CONE 60° DEGREE	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SJ-42M	3	2.5	3	38	S	●	●	
SJ-1M	6	4	6	50	S	●	●	
SJ-3M	9.5	8	6	55	B	●	●	
SJ-5M	12.7	11	6	56	B	●	●	
SJ-6M*	16	14.5	6*	61	B	●	●	
SJ-7M*	19	17.5	6*	65	B	○	○	
SJ-9M*	25	24.5	6*	68	B	○	○	

CONE 90° DEGREE	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOILD (ROD) / BRZ	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SK-42M	3	1.5	3	38	S	●	●	
SK-1M	6	3	6	50	S	●	●	
SK-3M	9.5	4.7	6	52	B	●	●	
SK-5M	12.7	6.3	6	54	B	●	●	
SK-6M*	16	8	6*	57	B	●	●	
SK-7M*	19	9.5	6*	58	B	○	○	
SK-9M*	25	12.7	6*	60	B	○	○	

● - EX STOCK/QUICK DELIVERY 0 - LEAD TIME REQUIRED
 *- OPTIONAL SHANK 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye Protection!



Wear Hearing Protection!



Observe the recommended rotational speed, especially when using burs with long shanks!

CONE RADIUS END	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOLD (ROD) / BRZ	Radius Angle	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SL-41M	3	9.5	3	38	S		•	•	
SL-42M	3	12.7	3	38	S		•	•	
SL-42M L50	3	12.7	3	50	S	8°	•	•	
SL-42M L75	3	12.7	3	75	S	8°	○	○	
SL-53M	5	12.7	3	50	S	14°	•	•	
SL-1M	6	16	6	50	S	14°	•	•	•
SL-1MB	6	16	6	60	B	14°	•	•	
SL-1M L150	6	16	6	166	B	14°	•	•	•
SL-2M	8	22	6	69	B	14°	•	•	
SL-3M	9.5	27	6	74	B	14°	•	•	•
SL-3M L150	9.5	27	6	177	B	14°	•	•	•
SL-4MZ	12	28	6	76	B	14°	•	•	
SL-4MZ L150	12	28	6	178	B	14°	•	•	
SL-4M	12.7	28	6	76	B	14°	•	•	•
SL-4M L150	12.7	28	6	178	B	14°	•	•	•
SL-5M*	16	30	6*	77	B	14°	•	•	
SL-7M*	19	38	6*	85	B	14°	•	•	

CONICAL	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOLD (ROD) / BRZ	Radius Angle	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SM-41M	3	8.9	3	38	S	12°	•	•	
SM-42M	3	11	3	38	S	14°	•	•	
SM-42M L50	3	11	3	50	S	14°	•	•	
SM-42M L75	3	11	3	75	S	14°	•	•	
SM-43M	3	16	3	38	S	7°	•	•	
SM-53M	5	12.7	3	38	S	16°	○	○	
SM-1M	6	12.7	6	50	S	22°	•	•	
SM 1MB	6	12.7	6	56	B	22°	•	•	
SM-2M	6	19	6	50	S	14°	•	•	
SM-2MB	6	19	6	63	B	14°	•	•	
SM-3M	6	25	6	50	S	10°	•	•	
SM-3MB	6	25	6	70	B	10°	•	•	
SM-51M	6.3	12.7	3	53	B	22°	•	•	
SM-4M	9.5	16	6	63	B	28°	•	•	
SM-5MZ	12	22	6	69	B	28°	•	•	
SM-5M	12.7	22	6	69	B	28°	•	•	
SM-6M*	16	25	6*	73	B	31°	•	•	○

ORDERING CODE:

SA-5 DC- Inch Shank, Burr -Cylindrical Shape, Double Cut
 SA-5M DC – Metric Shank, Burr -Cylindrical Shape, Double Cut
 SA-5M 8 DC- Burr -Cylindrical Shape, Double Cut, 8 mm Dia Shank.
 SA-5M 150 mm- Burr -Cylindrical Shape, Single Cut, Metric 6mm
 Dia Shank, Shank Length 150 mm.
 Extended Reach Burrs – 50mm, 100mm, 150mm, 200mm, 250mm,
 300mm are Available.
 Other available cuts – Foundry cut -FC, Chip Breaker- CB, Coarse
 cut -CC, Fine cut - FC, Diamond- DIA, Steel Mill Cut- SMC, Inox Mill
 Cut –IMC.

INVERTED CONE	HEAD DIA (MM)	CUT LENGTH (MM)	SHANK DIA (MM)	OAL LENGTH (MM)	SOLD (ROD) / BRZ	Radius Angle	Single Cut (SC)	Double Cut (DC)	Aluminium Cut (NF)
SN-41M	2.5	3	3	38	S	10°	•	•	
SN-42M	3	4	3	38	S	10°	•	•	
SN-53M	5	6.3	3	38	S	10°	○	○	
SN-1M	6	8	6	50	S	10°	•	•	
SN-1MB	6	8	6	53	B	10°	•	•	
SN-51M	6.3	6	3	44	B	10°	•	•	
SN-2M	9.5	9.5	6	53	B	13°	•	•	
SN-4M	12.7	12.7	6	57	B	28°	•	•	
SN-6M*	16	19	6*	63	B	18°	○	○	
SN-7M*	19	16	6*	60	B	30°	○	○	

CUT TYPES



SC
Single Cut



DC
Double Cut



CB
Chip Breaker Cut



FINE
Diamond Cut



NF
Aluminum Cut



IMC
Inox Mill Cut



SMC
Steel Mill Cut

● - EX STOCK/QUICK DELIVERY 0- LEAD TIME REQUIRED
 *- OPTIONAL SHANK 8mm Metric.



www.P65Warnings.ca.gov



Wear Eye
Protection!



Wear Hearing
Protection!



Observe the recommended
rotational speed, especially when
using burrs with long shanks!

SHIBALLOY®

Address : 141, Sector-A, Zone-B, New Industrial Estate,
 Bhubaneswar-751010, Odisha, India,
 Mobile & Whats App- 9937044996, Email- shiballoy@yahoo.com

www.shiballoy.com